

Technical data

# HD 90



**Tandem rollers Series HD**

Tandem roller with two vibrating roller drums

**H181**

**HIGHLIGHTS**

- > Excellent view of the machine and the construction site
- > Ergonomic driver platform with rotatable seat operating unit and adjustable driver's seat
- > 3-point articulation for even weight distribution and excellent on-centre feel
- > Track offset for comfortable start up, moving away and compacting at curb edges
- > Simple, intuitive and language-neutral operation

## TECHNICAL DATA HD 90 (H181)

## Weights

Operating weight with cab	kg	9190
Operating weight with ROPS	kg	8925
Max. operating weight	kg	11840
Static linear load, front/rear	kg/cm	27,6/27,1
French classification, value/class		22,4/VT1

## Machine dimensions

Total length	mm	4600
Total height with cab	mm	3040
Height loading, min.	mm	2360
Centre distance	mm	3400
Total width with cab	mm	1810
Maximum working width	mm	1780
Kerb clearance, left/right	mm	790/790
Turning radius, inside	mm	4500

## Drum dimensions

Drum width, front/rear	mm	1680/1680
Drum diameter, front/rear	mm	1200/1200
Drum thickness, front/rear	mm	17/17
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	100

## Diesel engine

Manufacturer		DEUTZ
Model		TCD 2012 L04 2V
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		100,0/136,0/2300
Power SAE J1349, kW/HP/rpm		100,0/134,0/2300
Exhaust emission standard		EU Stage IIIA / EPA Tier 3

## Travel drive

Speed, working gear	km/h	0-7,4
Speed, transport gear	km/h	0-14,8
Gradeability, with/without vibration	%	30/40

## Vibration

Vibration frequency, front, I/II	Hz	42/50
Vibration frequency, rear, I/II	Hz	42/50
Amplitude, front, I/II	mm	0,66/0,37
Amplitude, rear, I/II	mm	0,66/0,37
Centrifugal force, front, I/II	kN	75/60
Centrifugal force, rear, I/II	kN	75/60

## Steering

Swing angle +/-	°	10
Steering, type		Articulated steering

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L	185
Water tank, capacity	L	700

## Sound level

Sound power level L(WA), representative measurement	db(A)	105
---	-------	-----

## EQUIPMENT

2 x drive levers | Switchable amplitude: Big/small | Left/right handrails | Lighting package for driving on public roads | Driver's platform with entry from both sides | Seat operating unit, rotatable | Seat operating unit, rotatable, with armrests and seat belt | Vibration front and rear, single and double, switchable

## OPTIONAL EQUIPMENT

Air conditioning | Tachograph | Fire-extinguisher | Protective roof | Edge pressing and cutting equipment | Frequency regulation | HCQ compaction meter | Speedometer | Back-up alarm (reversing) | Telematics interface | Automatic vibration system | Working lights | Rotating beacon | Locking device | Tool kit